

IN THE CLAIMS

1. (Previously Presented) Apparatus for transferring an article from a first position to a second position without varying an angular orientation of the article, said apparatus comprising, in combination:

a fixed shaft;

a housing journaled on said fixed shaft to be oscillatable with respect to said fixed shaft;

a first gear within said housing, said first gear being co-axial with said fixed shaft and being oscillatable with respect to said fixed shaft, said first gear having a plurality of teeth in an outer periphery;

a rotatable shaft mounted within said housing;

a second gear fixed to said rotatable shaft within said housing and oscillatable with said housing, said second gear being spaced from said first gear and being rotatable with respect to said housing about a central axis of said second gear, said central axis of said second gear being parallel to the axis of oscillation of said first gear;

a rack extending through said housing and having a plurality of teeth in engagement with teeth on said first gear and teeth on said second gear; and

resilient biasing means for resiliently biasing said rack into engagement with said first gear and said second gear to minimize backlash between said first gear and said second gear.

2. (Original) Apparatus according to claim 1, wherein said biasing means comprises:

a first spring-mounted roller engaging said rack at a location opposed to and aligned with a central axis of said first gear; and

a second spring-mounted roller engaging said rack at a location opposed to and aligned with a central axis of said second gear.

3. (Original) Apparatus according to claim 1 and further comprising:
a reversible a.c. servo motor for oscillatingly driving said first gear.

4. (Currently Amended) Apparatus according to claim 1 ~~wherein:~~
~~_____ said article is a hot, freshly formed glass container and~~ further including a mold of an I.S. glass container forming machine at said first position and a deadplate of said I.S. glass container forming machine at said second position.

5. (Previously Presented) The method of providing a parallel motion to an end of an arm that is oscillatable about an axis spaced from said end to prevent varying of an angular position of said end during oscillation of the arm, the method comprising:

providing a first gear with a plurality of teeth on a periphery thereof, the first gear being coaxial with the axis of oscillation of the arm, the first gear being oscillatable with the arm;

providing a second gear with a plurality of teeth on a periphery of the second gear, the second gear being spaced from the first gear, the second gear being oscillatable with the arm and rotatable with respect to the arm about an axis that is spaced from the axis of oscillation of the arm;

simultaneously engaging the first gear and the second gear with a rack having a plurality of teeth in engagement with teeth on the first gear and teeth on the second gear; and

resiliently biasing the rack into engagement with the first gear and the second gear.

6. (Currently Amended) The method according to claim 5 wherein ~~the article is a hot, freshly formed glass container and~~ the arm is a takeout arm of an I.S. glass container forming machine.

7. (Original) The method according to claim 6 and further comprising:
operating the arm in an environment where the temperature exceeds 185°F.

8. (Original) The method according to claim 7 wherein the temperature is at least 225°F.